



DECLARATION OF PERFORMANCE

DoP No. 106



- 1 Product Type: **Consolite Easi-Lay - 10.4N**
 2 Identification: **151626**
 3 Intended use: **Walls and partitions**
 4 Manufacturer: **CCP Building Products Ltd., Llay Road, Llay, Wrexham, LL12 0TL**
 5 Authorised representative: **Not applicable**
 6 AVCP: **System 4**
 7 Harmonised Standard: **EN 771 - 3 : 2011**
 8 ETA: **Not applicable**
 9 Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length (mm)	440	EN 771 - 3 : 2011
	Width (mm)	140	
	Height (mm)	140	
Dimensional Tolerance		D1 (Flatness NPD, Plane Parallelism NPD)	
Configuration	Shape & Features	NPD	
	Group according to EN 1996-1-1 (EC6)	Group 1	
Compressive Strength	Mean Compressive Strength (N/mm ²)	10.4N [\perp bed face, whole unit (CatII)]	
	Direction of Load	Perpendicular to the bed faces	
	Unit Category	Category II	
Dimensional Stability Moisture Movement (mm/m)		0.6	
Bond Strength	Shear Bond Strength (N/mm ²)	0.15 with GPLM	
	Flexural Bond Strength	NPD	
Reaction to Fire		A1 (Commission Decision 2000/605/EC)	
Water Absorption, gm ² .s-0.5		NPD	
Water vapour permeability		5/15 (Tabulated Fixed Value EN 1745)	
Direct Airborne Sound Insulation	Gross Density (kg/m ³)	1850 - 2000	
	Configuration; dimensions & tolerances	See Configuration	
Thermal Conductivity, W /m.K ($\lambda_{10,dry}$)		1.13	
Resistance to freeze / thaw		For use above & below ground	
Dangerous Substances		See Note	

Note: Information on Dangerous substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011.

10 The performance of the product identified in 1 and 2 is in conformity with the declared performance in (9).

Signed on behalf of CCP Building Products Ltd

Peter Whalley

P Whalley (Group MRQEH) - Building Products Group Ltd; Llay, LL12 0TL

CCP

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in (4).



CCP BUILDING PRODUCTS LTD

Reg. Office: Llay Road, Llay, Wrexham LL12 0TL
106

BS EN 771-3:2011

Consolite Easi-Lay - 10.4N

Category II aggregate concrete masonry units

Dimensions (mm):	Length:	440
	Width:	140
	Height:	140
Dimensional Tolerance:	Category:	D1 (sect 5.2.2.1 of std)
	Flatness:	NPD
	Parallelism:	NPD
Configuration:	Shape / Features:	NPD
	Group according to BS EN 1996-1-1:	Group 1
Compressive strength:	Mean compressive strength:	10.4N/mm ² [\perp bed face]
	Direction of load:	90° to bed
Dimensional Stability:	Moisture movement:	0.6 mm/m
	Shear bond strength:	0.15 N/mm ²
Flexural bond strength:	Flexural bond strength:	NPD
	Unit category:	Category II
Water Absorption:		NPD
Reaction to fire		Euroclass A1
Water vapour diffusion coefficient:		5/15 (Tabulated EN 1745)
Direct airborne sound insulation:	Gross density:	1850 - 2000 kg/m ³
	Configuration:	See configuration (above)
Thermal conductivity:		1.13 W /m.K ($\lambda_{10,dry}$)
Durability against freeze/thaw:		Not to be left exposed
Dangerous Substances:		See note below

Note: Information on Dangerous substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011.

www.cheshireconcrete.co.uk

QA106/Iss01/Rev01 - May 2016