



# DECLARATION OF PERFORMANCE

DoP No. 105



- 1 Product Type: **Easi-Lay - 7.3N**
- 2 Identification: **151616**
- 3 Intended use: **Walls and partitions**
- 4 Manufacturer: **CCP Building Products Ltd., Llay Road, Llay, Wrexham, LL12 0TL**
- 5 Authorised representative: **Not applicable**
- 6 AVCP: **System 4**
- 7 Harmonised Standard: **EN 771 - 3 : 2011**
- 8 ETA: **Not applicable**
- 9 Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length (mm)	440	EN 771 - 3 : 2011
	Width (mm)	140	
	Height (mm)	140	
Dimensional Tolerance		D1 (Flatness NPD, Plane Parallelism NPD)	
Configuration	Shape & Features	NPD	
	Group according to EN 1996-1-1 (EC6)	Group 1	
Compressive Strength	Mean Compressive Strength (N/mm <sup>2</sup> )	7.3N [ $\perp$ bed face, whole unit (CatII)]	
	Direction of Load	Perpendicular to the bed faces	
	Unit Category	Category II	
Dimensional Stability Moisture Movement (mm/m)		0.6	
Bond Strength	Shear Bond Strength (N/mm <sup>2</sup> )	0.15 with GPLM	
	Flexural Bond Strength	NPD	
Reaction to Fire		A1 (Commission Decision 2000/605/EC)	
Water Absorption, gm <sup>2</sup> .s-0.5		NPD	
Water vapour permeability		5/15 (Tabulated Fixed Value from EN 1745)	
Direct Airborne Sound Insulation	Gross Density (kg/m <sup>3</sup> )	1850 - 2000	
	Configuration; dimensions & tolerances	See Configuration	
Thermal Conductivity, W /m.K ( $\lambda_{10,dry}$ )		1.13	
Resistance to freeze / thaw		For use above & below ground	
Dangerous Substances		See Note	

Note: Information on Dangerous substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011.

10 The performance of the product identified in 1 and 2 is in conformity with the declared performance in (9).

Signed on behalf of CCP Building Products Ltd

*Peter Whalley*

P Whalley (Group MRQEH) - Building Products Group Ltd; Llay, LL12 0TL

CCP

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in (4).



## CCP BUILDING PRODUCTS LTD

Reg. Office: Llay Road, Llay, Wrexham LL12 0TL  
105

BS EN 771-3:2011

### Easi-Lay - 7.3N

Category II aggregate concrete masonry units

<b>Dimensions (mm):</b>	Length:	440
	Width:	140
	Height:	140
<b>Dimensional Tolerance:</b>	Category:	D1 (sect 5.2.2.1 of std)
	Flatness:	NPD
	Parallelism:	NPD
<b>Configuration:</b>	Shape / Features:	NPD
	Group according to BS EN 1996-1-1:	Group 1
<b>Compressive strength:</b>	Mean compressive strength:	7.3N/mm <sup>2</sup> [ $\perp$ bed face]
	Direction of load:	90° to bed
		Unit category: Category II
<b>Dimensional Stability:</b>	Moisture movement:	0.6 mm/m
	Shear bond strength:	0.15 N/mm <sup>2</sup>
<b>Flexural bond strength:</b>	Flexural bond strength:	NPD
<b>Water Absorption:</b>	NPD	
<b>Reaction to fire</b>	Euroclass A1	
<b>Water vapour diffusion coefficient:</b>	5/15 (Tabulated EN 1745)	
<b>Direct airborne sound insulation:</b>	<b>Gross density:</b>	1850 - 2000 kg/m <sup>3</sup>
	<b>Configuration:</b>	See configuration (above)
<b>Thermal conductivity:</b>	1.13 W /m.K ( $\lambda_{10,dry}$ )	
<b>Durability against freeze/thaw:</b>	Not to be left exposed	
<b>Dangerous Substances:</b>	See note below	

Note: Information on Dangerous substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011.

www.ccp.ltd

QA105/Iss01/Rev01 - May 2016