



# DECLARATION OF PERFORMANCE

DoP No. 101



- 1 Product Type: **Solid Dense - 7.3N**
- 2 Identification: **As per delivery note description: 351310 (75mm) - 351410 (100mm) - 351610 (140mm)**
- 3 Intended use: **Foundations, walls and partitions**
- 4 Manufacturer: **CCP Building Products Ltd., Llay Road, Llay, Wrexham, LL12 0TL**
- 5 Authorised representative: **Not applicable**
- 6 AVCP: **System 4**
- 7 Harmonised Standard: **EN 771 - 3 : 2011**
- 8 ETA: **Not applicable**
- 9 Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length (mm)	440	EN 771 - 3 : 2011
	Width (mm)	75 / 100 / 140 - See delivery documentation	
	Height (mm)	215	
Dimensional Tolerance		D1 (Flatness NPD, Plane Parallelism NPD)	
Configuration	Shape & Features	NPD	
	Group according to EN 1996-1-1 (EC6)	Group 1	
Compressive Strength	Mean Compressive Strength (N/mm <sup>2</sup> )	7.3N [ $\perp$ bed face, whole unit (CatII)]	
	Direction of Load	Perpendicular to the bed faces	
	Unit Category	Category II	
Dimensional Stability Moisture Movement (mm/m)		0.6	
Bond Strength	Shear Bond Strength (N/mm <sup>2</sup> )	0.15 with GPLM	
	Flexural Bond Strength	NPD	
Reaction to Fire		A1 (Commission Decision 2000/605/EC)	
Water Absorption, gm <sup>2</sup> .s <sup>-0.5</sup>		NPD	
Water vapour permeability		5/15 (Tabulated Fixed Value from EN 1745)	
Direct Airborne Sound Insulation	Gross Density (kg/m <sup>3</sup> )	1850 - 2000	
	Configuration; dimensions & tolerances	See Configuration	
Thermal Conductivity, W /m.K ( $\lambda_{10}$ ,dry)		1.13	
Resistance to freeze / thaw		For use above & below ground	
Dangerous Substances		See Note	
<p>Note: Information on Dangerous substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011.</p>			

10 The performance of the product identified in 1 and 2 is in conformity with the declared performance in (9).

Signed on behalf of CCP Building Products Ltd

*Peter Whalley*

P Whalley (Group MRQEH) - Building Products Group Ltd; Llay, LL12 0TL

CCP

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in (4).



## CCP BUILDING PRODUCTS LTD

Reg. Office: Llay Road, Llay, Wrexham LL12 0TL

101

BS EN 771-3:2011

### Solid Dense - 7.3N

Category II aggregate concrete masonry units

Dimensions (mm):	Length:	440
	Width(s):	75 - 100 - 140
	Height:	215
Dimensional Tolerance:	Category:	D1 (sect 5.2.2.1 of std)
	Flatness:	NPD
	Parallelism:	NPD
Configuration:	Shape / Features:	NPD
	Group according to BS EN 1996-1-1:	Group 1
Compressive strength:	Mean compressive strength:	7.3N/mm <sup>2</sup> [ $\perp$ bed face]
	Direction of load:	90° to bed
Dimensional Stability:	Moisture movement:	0.6 mm/m
Flexural bond strength:	Shear bond strength:	0.15 N/mm <sup>2</sup>
	Flexural bond strength:	NPD
Water Absorption:		NPD
Reaction to fire		Euroclass A1
Water vapour diffusion coefficient:		5/15 (Tabulated EN 1745)
Direct airborne sound insulation:	Gross density:	1850 - 2000 kg/m <sup>3</sup>
	Configuration:	See configuration (above)
Thermal conductivity:		1.13 W /m.K ( $\lambda_{10}$ ,dry)
Durability against freeze/thaw:		Not to be left exposed
Dangerous Substances:		See note below

Note: Information on Dangerous substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-3:2011.

www.ccp.ltd

QA101/Iss01/Rev01 - May 2016