

Declaration of Performance



DoP Number	DOP-QMS-LL-021
Product Code	152610
Product Name	Cellular Dense 7.3N
Thickness	140 mm

Dimension	440mm x 215mm
Dimensional tolerances	
Category	D1
Flatness	NPD
Plane parallelism	NPD
Configuration	Group 1 unit to EN 1996-1-1 (Cellular)
Compressive strength	7.3 N/mm²
Dimensional stability	<0.6mm/m
Shear bond strength	0.15 N/mm²
Flexural bond strength	NPD
Reaction to fire	Euroclass A1
Water absorption	NPD
Water vapour diffusion coefficient	Fixed value $\mu = 5/15$
Direct airborne insulation	
Gross dry density	1850-2000 Kg/m ³
Configuration	Group 1 unit to EN 1996-1-1 (Cellular)
Thermal conductivity	0.86 W/mk
Durability against freeze/thaw	Not to be left exposed
Dangerous substances	Information on dangerous substances will only be given when and where required and in the appropriate form (see EN771-3, ZA 3). (see material data sheets)

This Declaration of Performance is issued under the sole responsibility to the manufacturer as identified above.

Signed for and on behalf of the manufacturer by:

Matthew Keegan - CCP Operations Manager

EN771-3:2011

CCP Building Products Ltd

Llay Rd | Llay | Wrexham | LL12 0TL

01978 799070 | ccp@ccp.ltd | www.ccp.ltd